



HI TECH ENTERPRISE

A HOUSE OF INDUSTRIAL HARDWARE



Office :
Shop No. 36/1/18, Abhishek Complex, Opp. BOB, GIDC,
Vadsar Road, Makarpura, Vadodara-390010.

Vishal Patel : 9879911483
Jatin Patel : 9099820173
Email : hitech.enter2018@gmail.com



• JAW FLEX COUPLING :

Type - L / SW / RRL / RRS / RFC / RRJ / RN

• TYRE COUPLING :

Type - T / TO / RST

• PIN BUSH COUPLING :

Type - RB / LBC / RC / RCT

• GEAR COUPLING :

Type - LFG / LHG, AGMA Std. RGD / RGS

• GRID COUPLING :

Type - LFG / RGT

• DISC-O-FLEX COUPLING :

Type - LM / EM / LMK / EMT / EMD / RSK

• POLY GEAR COUPLING :

Type - RPG

• RIGID COUPLING :

Type - RR / RGR

• DRIVE (CARDON) SHAFT COUPLING :

Type - RDC

• HELIFLEX COUPLING :

Type - RSB/ RCB / RSD / RCD

ANTI-VIBRATION MOUNTS

POLYBOND

ANTI-VIBRATION MOUNTINGS

- COMBIMOUNT - PS, PC & PCS
- O-MOUNT
- SUPER MOUNT
- PGS & PDM MOUNT
- SANDWICH MOUNT
- CORE MOUNT - PSC, P & PML
- MACHINE MOUNT
- MACHINERY RUBBER PADS





CHAMPION GASKET SHEET

SPITMAAN®

ASBESTOS FIBRE JOINTING SHEET

**Style 20 Non Metallic**

Recommended Max. Temp. 380° C
 Recommended Max. Pres. 35 Kg/Cm²
 Spec. Compliance : IS 2712-1998
 Grade W/3, IS 2712-1971 Grade C

**Style 54 Non Metallic**

Recommended Max. Temp. 550° C
 Recommended Max. Pres. 150 Kg/Cm²
 Spec. Compliance : IS 2712-1998
 Grade W/1, IS 2712-1971 Grade A/S
 British BS 2815-1973 Grade A

**Style 59 Oil**

Recommended Max. Temp. 550° C
 Recommended Max. Pres. 150 Kg/Cm²
 Spec. Compliance : IS 2712-1998
 Grade O/1, IS 2712-1971 Grade A/O
 Defense TS RED/71/59, British BS 1832-1972

**Style 60 Acid**

Recommended Max. Temp. 210° C
 Recommended Max. Pres. 150 Kg/Cm²
 Spec. Compliance : IS 2712-1998
 Grade A/1

CHAMPION JOINTINGS PVT. LTD.

NON ASBESTOS JOINTING SHEET

**Style AF 120 Non Metallic**

Max. Operating Pressure 50 Bars
 Max. short term Service Temp. 250° C
 Max. Continuous Service Temp. 180° C

**Style AF 154 Non Metallic**

Max. Operating Pressure 150 Bars
 Max. short term Service Temp. 350° C
 Max. Continuous Service Temp. 250° C

**Style AF 159 Oil**

Max. Operating Pressure 150 Bars
 Max. short term Service Temp. 450° C
 Max. Continuous Service Temp. 250° C

**Style AF 160 Acid**

Max. Operating Pressure 120 Bars
 Max. short term Service Temp. 250° C
 Max. Continuous Service Temp. 210° C

SPITMAAN CUT GASKETS & SPIRAL WOUND GASKETS



Cut Ring, Full Face, Spiral Wound, Envelope, Jacketed, Ring Joints & As per Customer Requirement.

GLAND PACKINGS

SPITMAAN®

- ASBESTOS & CERAMIC DRY GLAND & ROPE
- ASBESTOS GRAPHITE GLAND
- PTFE IMPREGNATED GLAND
- PURE PTFE & GRAPHITE PTFE GLAND
- PTFE FLEX-O-SEAL PACKING
- PTFE UNIVERSAL ROPE
- PTFE THREAD SEALANT TAPE
- GREPHOIL TAPE & RING
- BRAKE LINER & HAIR BELT
- ASBESTOS & CERAMIC WEBBING TAPE



TRANSMISSION PRODUCTS



• BELT :

Classical Belt (A/B/C/D/E/Z)
Wedge Belt (SPA/SPB/SPC/SPZ, 3V/5V/8V)
Ribbed Belt (PJ/PK/PL/PM)
Timing Belt (MXL/XL/L/H/XH)
HiTD Belt (2M/3M/5M/8M/14M)
Variable Speed Belt & Conveyor Belt

• PULLEY :

Classical Belt Pulley
Wedge Belt Pulley
HiTD Belt Pulley
Timing Belt Pulley

• CHAIN :

Roller Chain (ISO/BS, DIN, ANSI & API Certified)
Conveyor & Silent Chain, Leaf & Oil Field Chain

• CHAIN SPROCKET :

Harden Teeth Sprocket

• TAPER LOCK BUSH :

Pilot Bore & Finish Bore

• SEALS :

Oil Seal, Hydraulic Seal & Special Seal

• BEARING :

Ball, Roller & Spherical Bearing & Plummer Block

FRENZELIT GASKET SHEETS



- PURE EXPANDED PTFE GASKET SHEET
- PURE GRAPHITE GASKET SHEET
- PURE GRAPHITE WITH SS INSERT
- GASKET SHEET
- NON ASBESTOS METALLIC / NON METALLIC
- GASKET SHEET





FASTENERS



- **BOLT** : Hex, Allen Cap, Eye Bolt, U-Bolt, J-Hook, L-Hook, Anchor Fastener & Foundation.
- **NUT** : Hex, Nylock, Dom, Wing & Lock.
- **SCREW** : CSK, Grub, Round Head, Cheese Head, Button Head & Phillips Head.
- **STUD** : Full Thread & Half Thread.
- **WASHER** : Plain, Spring, Tapper, Disc & Square.
- **PLATING & COATING** : GI, Hot Dip, Cadmium, Nickle, Lead, PP & Teflon Coating.
- **GRADE** : 4.6, 8.8, 10.9, 12.9, ASTM A193 B7 & A194 2H, L7, B7M, A2-70, A4-80, 8M, B16
- **MOC** : MS, SS, High Tensile, Brass, Copper, Hastelloy, Incolloy, Nickle, Titanium.

ADHESIVES & MAINTENANCE PRODUCTS



LOCTITE



Stanvac

- **ADHESIVE** : Loctite, Belzone, Pidilite, Anabond, Araldite, Dow Corning & Speb-7
- **MAINTENANCE PRODUCT** : WD-40, CRC 226, Rustlick, Rustolene, OKS, Molicote, Mosil & All Lubrication Products.



TOOLS & WELDING ACCESSORIES



Mitutoyo



MIRANDA

HACKSAWS & TOOL BITS



- **TAPARIA** : Hand Tools
- **MITUTOYO** : Measuring Instruments
- **MIRANDA** : HSS & Carbide Cutting Tools
- : HSS & Bimetal Hacksaw Blades
- **TOTEM** : Tap Sets & Round Die
- **ESAB** : Welding Rod & Accessories
- **BOSCH** : Power Tools, Grinding & Cutting Wheel & Abrasives Product

PTFE (TEFLON) PRODUCTS



- **ROD :**
03 mm to 300 mm Dia & 300 mm to 1000 mm Length.
- **BUSH :**
06 mm to 1000 mm ID & 100 mm to 500 mm Length.
- **SHEET :**
300 X 300 mm to 2000 X 2000 mm &
0.25 mm to 100 mm Thickness
- **TUBING :** 1.6 mm to to 100 mm ID
- **BELLOW :**
Line Bellow, As per QVF Std. - ½" to 12"
- **BALL :** 03 mm to 100 mm Dia.
- **GASKET :** Envelope & Solid Gasket, Size - ½" to 12"
- **DIAPHRAGM :** Teflon Line Diaphragm in Pin Type &
Screw Type. Size - ½" to 12"
- **MOC :**
PTFE, GFT, CFT, Nylon, PP, UHMWPE, Delrin & Bakelite.

RUBBER PRODUCTS

- SHEET
 - TUBING & PROFILE
 - O-RING & O-RING CODE
 - OIL SEAL, V-SEAL & HYDRAULIC SEAL
 - DOUTY SEAL
 - BELLOW
 - DIAPHRAGM
 - TRI-CLOVER GASKET
 - FDB GASKET
 - SPONGE & RIGID STRIPS
 - HYDRAULIC SEAL
 - ALL TYPE OF RUBBER PRODUCT
- MANUFACTURER

- MOC :**
- NATURAL, NITRILE, NEOPRENE, SILICON,
VITON, EPDM, PU, BUTYL & HYPLON.



ALL TYPE OF RUBBER PRODUCT MANUFACTURER



VALVES

FlowTek

Parth



- **TYPE :** Ball Valve, Gate Valve, Globe Valve, Strainer, NRV, PRV, Butterfly Valve, Foot Valve, Sight Glass Valve

- **MOC :** MS, CI, CS, SS, PP, HDPE, PVC.
- **CLASS :** ASA150# to 1500#, Table - D/E/F, ND-10/16/40
- **END Connection :** Flangend, Screwend & Socketweld.

PIPE & PIPE FITTINGS



Parth



- **PIPE :** ERW & Seamless, MS, GI, SS, HDPE, PP, PVC & UPVC. Class - A/B/C & Schedule - 10/40/80/160

- **FITTING :** Buttweld, Threaded & Socketweld Elbow, Flange, Tee, Reducer, Longbend, Ubend, Coupling, Hex & Hose Nipple, Union, Blind Plug.

LIFTING PRODUCTS



- Wire Rope & Wire Rope Slings
- D Shackle & Bow Shackle
- Eye Bolt & Eye Hook
- Thimble & Clamp
- Chain Pulley Block
- Turn Buckle
- **MOC :** PU, Nylon, Steel & Stainless Steel.





HOSES & HOSE CLIPS



- NYLON BRAIDED
- GREEN SUCTION
- DUCT HOSE
- WIRE REINFORCED
- STEAM
- CHEMICAL
- OIL HOSE
- AIR WATER
- TEFLON LINE
- SS CORRUGATED
- LOW & HIGH PRESSURE
- SS & MS HOSE CLIPS

PNEUMATIC & HYDRAULIC FITTINGS



- PU & NYLON TUBE
- PUSH, POS & AIRMETO FITTINGS
- FRL & CYLINDER
- MANYFOLD & SOLENOID VALVE
- CAMLOCK COUPLING
- QUICK RELEASE COUPLING
- PRESSURE GAUGE, TEMPERATURE GAUGE & ACCESSORIES
- PNEUMATIC ACTUATOR VALVES
- **MOC : PU, ALUMINUM, CS, SS, BRASS & COPPER.**



BRANCH OFFICE



Vishal Enterprise

Shop No. 3, Plot No. 582, Ward 12/C,
Police Station Road, Gandhidham - Kutch. 370201
M : 9558805524



Ankush Enterprise

Shop No. 6, Bansidhar Complex, Asian Paint Chowkdi,
G.I.D.C., Ankleshwar - 393 002. Gujarat (INDIA)